



**NOTE**

GI = Gas Inlet 3/4" BSP Male  
 WI = Water Inlet 15mm flared non-return isolating valve Female  
 Waste = 2" BSP Male  
 Drain = 2" BSP Female

Gas Consumption: NG = 150MJ/h; LPG = 150MJ/h

**UNLESS OTHERWISE SPECIFIED:**  
 1. DIMENSIONS ARE IN MILLIMETRES  
 2. TOLERANCES:  
 LINEAR: +/- 1mm  
 ANGULAR: +/- 0.30°  
 3. BEND RADII 2mm. ALL BENDS AT 90°

**SURFACE FINISH:**  
 1. NATURAL (LEAVE FILM INTACT FOR DELIVERY).  
 2. NO BLEMISHES OR SCRATCHES ON BASE METAL.  
 3. REMOVE ALL BURRS AND SHARP EDGES.



DO NOT SCALE DRAWING      REVISION: -

**B+S**      **B & S Commercial Kitchens**  
 57 Plateau Road, Reservoir Victoria, 3073  
 Tel.: (03) 9469 4754 / Fax: 9469 4504

TITLE:      **DSK-3**

DRAWN: S.K.      SIGNATURE:      DATE: 8/05/2023

CHK'D:      MATERIAL:      DWG NO.      **A3**

APPV'D:      WEIGHT:      SCALE: 1:15      SHEET 1 OF 1

MFG:      Q.A: