



NOTE

GI = Gas Inlet 3/4" BSP Male
 WI = Water Inlet 15mm flared non-return isolating valve Female
 Waste = 2" BSP Male
 Drain = 2" BSP Female

Gas Consumption: NG = 90MJ/h; LPG = 90MJ/h

UNLESS OTHERWISE SPECIFIED:
 1. DIMENSIONS ARE IN MILLIMETRES
 2. TOLERANCES:
 LINEAR: +/- 1mm
 ANGULAR: +/- 0.30°
 3. BEND RADIUS 2mm. ALL BENDS AT 90°

SURFACE FINISH:
 1. NATURAL (LEAVE FILM INTACT FOR DELIVERY).
 2. NO BLEMISHES OR SCRATCHES ON BASE METAL.
 3. REMOVE ALL BURRS AND SHARP EDGES.



DO NOT SCALE DRAWING		REVISION: -	
		B & S Commercial Kitchens 57 Plateau Road, Reservoir Victoria, 3073 Tel.: (03) 9469 4754 / Fax: 9469 4504	
		TITLE: DSK-3S	
DRAWN: S.K. CHK'D: APPV'D: MFG: Q.A:		DWG NO.: SCALE: 1:15 SHEET 1 OF 1	
THICKNESS (mm): MATERIAL: WEIGHT:		A3	