

RAPID FRYER SERIES: RF-1E

Single Pan Two Basket Electric Fryer - 13.5 Kilowatt


Project: _____ Item: _____





Standard Features:

- AISI Grade Stainless Steel
- · Heavy duty complete stainless steel frame
- Stainless steel constructed pans 2mm Thick
- Highly efficient heating elements
- Built-in thermal insulation layer saves energy and improves efficiency
- Easy to use programable display controller
- Over-temperature safety cut-out switch
- Temperature range: 90°C 190°C
- 40L oil capacity
- Inbuilt oil filtration system
- Removable oil collection tank
- Easily movable unit with lockable front castors
- Baskets Provided: 335mm L x 165mm W x 150mm H (2 per tank)
- Pan Dimensions: 340mm W x 410mm D x 385mm H (Height from base to max oil level mark is 280mm H)

Specifications:







MODEL	LENGTH	DEPTH	HEIGHT	NET WEIGHT	
	(mm)	(mm)	(mm)	(kg)	
RF-1E	450	900	1140	128	

Connections:

ELECTRICAL CONNECTION (EC)	ELECTRICAL SUPPLY REQUIREMENTS					
	VOLTAGE (V)	TYPE	FREQUENCY (Hz)	POWER (kW)	AMPS (A)	
Hard Wired	400	3P+N+E	50/60	13.5	20	

Must be installed by an authorised installer in accordance to AS/NZS 3000 refer to current version

Due to ongoing Product Development, Product Improvement and Research, B+S Commercial Kitchens reserves the right to alter specification without notice.

Electromagnetic Compatibility: AS/NZS CISPR 14.1, EN IEC 55014-1:2021



