



K+ SERIES: KBT-SB4-CBR6

Combination Four Open Burners & 600mm Char Broiler on Stand

Project:	Item:	
i iojoot.	ILCIII.	




Standard Features:


- AISI grade stainless steel
- · Heavy duty complete stainless steel frame with undershelf
- 30MJ removable two-piece open cooktop burner (BT)
- 34MJ stainless steel U-Burner per 300mm section (CBR)
- Heavy duty cast iron J-Grates & Radiant Hoods
- Reversible J-Grates allow for an inclined or flat cooking surface
- Flame failure device included as standard
- Piezo ignition to pilot char broiler burner
- Multi-setting gas valve allows greater regulation of flame settings
- Easy access to all components for servicing and adjustments
- Easy to clean fat spillage trays and rear splashback heat deflector


Options:

- NG/LPG Available in Natural or LP Gas
- PLT Pilot light per burner
- SPB Spillage Bowl
- BM Bench mounted
- CS Non-swivel rear castors Set of two

Specifications:







MODEL	LENGTH (mm)	DEPTH (mm)	HEIGHT (mm)	NET WEIGHT (kg)	GAS CONSUMPTION (MJ/h)	
					NG	LPG
KBT-SB4-CBR6	1200	840	1030	180	188	160

Connections:

GAS (GI)	SUPPLY PRESSURE (kPa)		
(BSP)	NG	LPG	
³ ⁄ ₄ " (M)	1.0	2.6	

- · Gas regulator is supplied with the unit
- The unit must be installed by an authorised installer in accordance to AS/NZS5601 refer to current version

Due to ongoing Product Development, Product Improvement and Research, B+S Commercial Kitchens reserves the right to alter specifications and the design of the product without notice.

Approval Number: GMK 10703





