

K+ SERIES: KBT-SB6 Six Burner Boiling Top on Stand

Project: _____ Item: _




Standard Features:


- AISI grade stainless steel •
- Heavy duty complete stainless steel frame with undershelf •
- 30MJ removable two-piece open cooktop burner •
- Heavy duty cast iron boiling top trivets ٠
- Flame failure device included as standard •
- Multi-setting gas valve allows greater regulation of flame settings
- Easy access to all components for servicing and adjustments
- Easy to clean fat spillage tray and rear splashback heat deflector


Options:

- NG/LPG Available in Natural or LP Gas .
- PLT Pilot light per burner
- SPB Spillage Bowl •
- BM Bench mounted •
- CS Non-swivel rear castors Set of two









MODEL	LENGTH (mm)	DEPTH (mm)	HEIGHT (mm)	NET WEIGHT (kg)	GAS CONSUMPTION (MJ/h)	
					NG	LPG
KBT-SB6	900	840	1030	115	180	150

Connections:

GAS (GI)	SUPPLY PRESSURE (kPa)			
(BSP)	NG	LPG		
³ ⁄4" (M)	1.0	2.6		

- Gas regulator is supplied with the unit
- The unit must be installed by an authorised installer in accordance to AS/NZS5601 refer to current version

Due to ongoing Product Development, Product Improvement and Research, B+S Commercial Kitchens reserves the right to alter specifications and the design of the product without notice.

Approval Number: GMK 10703





