



K+ SERIES: KBT-SB8 Eight Burner Boiling Top on Stand

Project: _____ Item: ____




Standard Features:


- AISI grade stainless steel
- · Heavy duty complete stainless steel frame with undershelf
- 30MJ removable two-piece open cooktop burner
- · Heavy duty cast iron boiling top trivets
- Flame failure device included as standard
- Multi-setting gas valve allows greater regulation of flame settings
- · Easy access to all components for servicing and adjustments
- Easy to clean fat spillage trays and rear splashback heat deflectors


Options:

- NG/LPG Available in Natural or LP Gas
- PLT Pilot light per burner
- SPB Spillage Bowl
- BM Bench mounted
- CS Non-swivel rear castors Set of two

Specifications:







Ī	MODEL	LENGTH (mm)	DEPTH (mm)	HEIGHT (mm)	NET WEIGHT (kg)	GAS CONSUMPTION (MJ/h)	
						NG	LPG
	KBT-SB8	1200	840	1030	150	240	200

Connections:

GAS (GI)	SUPPLY PRESSURE (kPa)			
(BSP)	NG	LPG		
³ ⁄ ₄ " (M)	1.0	2.6		

- Gas regulator is supplied with the unit
- The unit must be installed by an authorised installer in accordance to AS/NZS5601 refer to current version

Due to ongoing Product Development, Product Improvement and Research, B+S Commercial Kitchens reserves the right to alter specifications and the design of the product without notice.

Approval Number: GMK 10703





