



# K+ SERIES: KNC-CF

**Noodle Cooker with Cheung Fun Insert** 

Project: Item:
----------------




### **Standard Features:**


- AISI grade stainless steel
- AISI 316 Marine grade stainless steel tank 2mm Thick
- Efficient multi-jet target burner
- · In-built water overflow helps remove water impurities
- · Water temperature is thermostatically controlled
- 30L water capacity
- Flame failure device included as standard
- Piezo ignition to pilot the multi-jet target burner
- Manually operated water spindle to control tank refill
- Aluminium perforated steaming plate 5mm thick
- · Cheung fun adapter and lightweight lid provided
- Front access to all components makes service easy
- Pan Dimensions: 455mm D x 300mm W x 120mm H (Height is measured from the base plate to the water level mark)


## **Options:**

- NG/LPG Available in Natural or LP Gas
- CS Non-swivel rear castors Set of two

# **Specifications:**







	MODEL	LENGTH (mm)	DEPTH (mm)	HEIGHT (mm)	NET WEIGHT (kg)	GAS CONSUMPTION (MJ/h)	
						NG	LPG
	KNC-CF	450	840	1030	90	70	75

### **Connections:**

GAS (GI)	WATER (WI)	TANK DRAIN (D)	SUPPLY PRESSURE (kPa)		
(BSP)	(BSP)	OVERFLOW (OV)	NG	LPG	
<sup>3</sup> ⁄ <sub>4</sub> " (M)	½" (F)	D & OV = 1" BSP (M)	1.0	2.6	

- Combination control valve with an inbuilt regulator is supplied within the unit
- The unit must be installed by an authorised installer in accordance to AS/NZS5601 refer to current version

Due to ongoing Product Development, Product Improvement and Research, B+S Commercial Kitchens reserves the right to alter specifications and the design of the product without notice.

**Approval Number: GMK 10682** 





