

Oven with 900mm Grill Plate




Project: _____ Item: ___


Standard Features:


- AISI grade stainless steel •
- Heavy duty complete stainless steel frame •
- 22MJ aluminised tube burner per 300mm section (GRP) •
- 29MJ solid stainless steel tubular oven burner (OV) •
- Heavy duty mild steel grill plate (20mm Thick) •
- Top welded surface, smooth finish design
- Solid 6mm mild steel base plate allows for even heat distribution
- Heavy duty insulated drop down door with spring hinge system
- German manufactured thermostat ensures accurate temperature control
- Flame failure device included as standard
- Multi-setting gas valve allows greater regulation of flame settings
- Easy access to all components for servicing and adjustments
- Easy to clean fat spillage trays and rear splashback heat deflectors
- Largest gastronorm capacity in its class
- Internal Oven Dimensions: 630mm D x 785mm W x 290mm H • (Height is measured from the lowest rack position to the top panel)

Options:

- NG/LPG Available in Natural or LP Gas
- CS Non-swivel rear castors Set of two







	MODEL	LENGTH (mm)	DEPTH (mm)	HEIGHT (mm)	NET WEIGHT (kg)	GAS CONSUMPTION (MJ/h)	
						NG	LPG
	KOV-GRP9	900	840	1030	230	95	94

Connections:

Specifications:

GAS (GI)	SUPPLY PRESSURE (kPa)			
(BSP)	NG	LPG		
³∕₄" (F)	1.0	2.6		

- Gas regulator is supplied with the unit
- The unit must be installed by an authorised installer in accordance to AS/NZS5601 refer to current version

Due to ongoing Product Development, Product Improvement and Research, B+S Commercial Kitchens reserves the right to alter specifications and the design of the product without notice.

Approval Number: GMK 10703





