

K+ SERIES: KOV-SB2-GRP3

Combination Oven with Two Open Burners & 300mm Grill Plate

Project: _____ Item: ___



Standard Features:


- AISI grade stainless steel
- Heavy duty complete stainless steel frame •
- 30MJ removable two-piece open cooktop burner (BT) •
- 22MJ aluminised tube burner per 300mm section (GRP) •
- 29MJ solid stainless steel tubular oven burner (OV) •
- Heavy duty cast iron boiling top trivets •
- Heavy duty mild steel grill plate (12mm Thick)
- Solid 6mm mild steel base plate allows for even heat distribution
- Heavy duty insulated drop down door with spring hinge system •
- German manufactured thermostat ensures accurate temperature control
- Flame failure device included as standard
- Multi-setting gas valve allows greater regulation of flame settings
- Easy access to all components for servicing and adjustments
- Easy to clean fat spillage trays and rear splashback heat deflectors
- Largest gastronorm capacity in its class
- Internal Oven Dimensions: 630mm D x 485mm W x 290mm H (Height is measured from the lowest rack position to the top panel)


Options:


NG/LPG - Available in Natural or LP Gas • SPB - Spillage Bowl

030

- CS Non-swivel rear castors Set of two PLT Pilot light per burner







MODEL	LENGTH (mm)	DEPTH (mm)	HEIGHT (mm)	NET WEIGHT (kg)	GAS CONSUMPTION (MJ/h)	
					NG	LPG
KOV-SB2-GRP3	600	840	1030	150	111	100

Connections:

GAS (GI)	SUPPLY PRESSURE (kPa)			
(BSP)	NG	LPG		
³∕₄" (F)	1.0	2.6		

- Gas regulator is supplied with the unit
- The unit must be installed by an authorised installer in accordance to AS/NZS5601 refer to current version

Due to ongoing Product Development, Product Improvement and Research, B+S Commercial Kitchens reserves the right to alter specifications and the design of the product without notice.

Approval Number: GMK 10703





