# K+ SERIES: KOV-SB6

Six Burner Oven



900

-

000000

# Project: \_\_\_\_\_

\_\_ Item: \_\_

# **Standard Features:**


- AISI grade stainless steel
- Heavy duty complete stainless steel frame
- 30MJ removable two-piece open cooktop burner (BT)
- 29MJ solid stainless steel tubular oven burner (OV)
- Heavy duty cast iron boiling top trivets
- Solid 6mm mild steel base plate allows for even heat distribution
- Heavy duty insulated drop down door with spring hinge system
- German manufactured thermostat ensures accurate temperature control
- Flame failure device included as standard
- Multi-setting gas valve allows greater regulation of flame settings
- Easy access to all components for servicing and adjustments
- Easy to clean fat spillage tray and rear splashback heat deflector
- Largest gastronorm capacity in its class
- Internal Oven Dimensions: 630mm D x 785mm W x 290mm H (Height is measured from the lowest rack position to the top panel)


8

G

#### **Options:**

- NG/LPG Available in Natural or LP Gas
- PLT Pilot light per burner
- SPB Spillage Bowl
- CS Non-swivel rear castors Set of two





MODEL	LENGTH (mm)	DEPTH (mm)	HEIGHT (mm)	NET WEIGHT (kg)	GAS CONSUMPTION (MJ/h)	
					NG	LPG
KOV-SB6	900	840	1030	200	209	178

# **Connections:**

00

Π

GAS (GI)	SUPPLY PRESSURE (kPa)			
(BSP)	NG	LPG		
³∕₄" (F)	1.0	2.6		

- Gas regulator is supplied with the unit
- The unit must be installed by an authorised installer in accordance to AS/NZS5601 refer to current version

# Due to ongoing Product Development, Product Improvement and Research, B+S Commercial Kitchens reserves the right to alter specifications and the design of the product without notice.

# Approval Number: GMK 10703





