



K+ SERIES: KNC-6 Six Basket Noodle Cooker

Project:	Item:
1 10,00.	ILGIII.




Standard Features:


- AISI Grade Stainless Steel
- AISI 316 Marine grade stainless steel tank 1.5mm Thick
- Efficient multi-jet target burner
- · In-built water overflow helps remove water impurities
- Water temperature is thermostatically controlled
- 30L water capacity
- Flame Failure Included as standard
- Piezo ignition to pilot multi-jet target burner
- Noodle baskets provided
- Front access to all components makes service easy
- Pan Dimensions: 455mm D x 300mm W x 120mm H
 (Height is measured from the base plate to water level mark)


Options:

- · Natural or LPG Gas
- Non-swivel rear castors Set of two

Specifications:







	MODEL	LENGTH (mm)	DEPTH (mm)	HEIGHT (mm)	NET WEIGHT (kg)	GAS CONSUMPTION (Mj/h)	
						NG	LPG
	KNC-6	450	840	1030	-	70	75

Connections:

GAS (GI)	WATER	DRAIN (D)	SUPPLY PRE	SSURE (kPa)
(BSP)	(WI)	OVERFLOW (OV)	NG	LPG
³ ⁄ ₄ " (F)	½" (Copper)	D & OV = 1" BSP (M)	1.0	2.6

- Combination control valve with inbuilt regulator is supplied within the unit
- Must be installed by an authorised installer in accordance to AS/NZS5601 refer to current version

Due to ongoing Product Development, Product Improvement and Research, B+S Commercial Kitchens reserves the right to alter specification without notice.

Approval Number: GMK 10682





