



VERRO SERIES: VOV-TT9

Oven with 900mm Target Top

Project:	Item:



Standard Features:


- AISI Grade Stainless Steel
- · Heavy duty complete stainless steel frame
- 42MJ dual ring cast iron burner (TT)
- 29MJ solid stainless steel tubular oven burner (OV)
- Three piece heavy duty machined cast iron top with removable center ring
- Internal lining consisting of thermal insulating refractory bricks that offers low heat conductivity and integral spill protection
- Surface cooking area 900mm W x 620mm D
- Solid mild steel base plate allows for even heat distribution
- Heavy duty insulated drop down door with spring hinge system
- German manufactured thermostat ensures accurate temperature control
- Flame Failure Included as standard
- Multi-setting gas valve Allows greater regulation of flame setting
- Easy access to all components for servicing and adjustments
- Easy to clean fat spillage tray
- Largest gastronorm capacity in its class


Non-swivel rear castors - Set of two

 Internal Oven Dimensions: 630mm D x 785mm W x 290mm H (Height is measured from lowest rack position to the top panel)


Options:

Specifications:





Natural or LPG Gas



Fan Forced

MODEL	LENGTH	DEPTH	HEIGHT	NET WEIGHT	GAS CONSUMPTION (Mj/h)	
WODEL	(mm)	(mm)	(mm)	(kg)	NG	LPG
VOV-TT9	900	840	1030	-	71	70

Connections:

GAS (GI)	FAN FORCED OPTION	SUPPLY PRESSURE (kPa)		
(BSP)	ELECTRICAL CONNECTION (EC)	NG	LPG	
³ ⁄ ₄ " (F)	10A 250V~ 1.2m Plug 240V AC 50Hz 30W Fan	1.0	2.6	

- · Gas regulator is included with the unit
- Must be installed by an authorised installer in accordance to AS/NZS5601 refer to current version

Due to ongoing Product Development, Product Improvement and Research, B+S Commercial Kitchens reserves the right to alter specification without notice.

Approval Number: GMK 10686





